

R120 ORDER FORM

SYST	ЕМ	- 1	NTERN	AL USE	E		INTERNAL OR EXTERNAL													_			Q			
			no								GC30		Ш	□ GC		of 🛄		ELECTRIC DRIVE		DRIVE	MECHANICAL STOPS	ELECTRONIC STOPS	RATIO	STANDARD	ELERO	SOMFY
SIDE GUIDE		SIONS	sid	side guide				able 2.5	SNOI	GC30R FIXED TO THE FRAME				E GC3		FD 🎞			AXIS		Σ	0		DM45S	VariEco	JET
BOTTOM		MAXIMUM DIMENSIONS	3	5	E	IMENS	6	20[]3	MAXIMUM DIMENSIONS	05	9	707	₩,	25	B	∕ 2√			NEMO			Х			SUNTOP	ALTUS WT
	Z X X		\bigcirc	\bigcirc	12 12	MAXIMUM DIMENSIONS				fi42 (fi42+ PPW C	20	أسأا	\cup	\cup	[] 20 1	للسا		NEM)		Х	Х	DM45EAF/S	SUNTOP 868	ALTUS RTS
			fi35	fi42	FG42 MAXIMUN	MAXII	fi42	FG120				FG1	FG120+ PPW	fi42	fi42+ PPW	FG120	FG120+ PPW		NEMO IO homecontrol			Х	X			SUNILUS io
120		4,0x 4,0				3,5x			4,0x								•	SYSTE SOLU	QUARE SYME EM TYPE MEA TION.	OL IN THE T NS THAT TH	OP RIGHT E SYSTEM	CORNER OF EXISTS AS S	THE FIELD TANDARD A	WHERE YOU S A SELF-S	J CHOOSE 1 JPPORTING	THE 3
120 PL	120 UNDER PLASTER				L_	3,0			4,0											OF THE SYS			ASTER COMES NOT PAINTED AS A		TED AS A S	TANDARD
COLLEC	TION	VSR	RAL	RAL	RAL	RAL	RAL	RAL	RAL	RAL	RAL	RAL	RAL	DB	FSM	RAL	RAL	RAL	RAL	RAL	RAL	RAL	VSR	RED RAL	RAL	RAL
COLOI SYSTI CONSTRU	EM	240	1015	1013	9001	9010	9016	7035	9006	7001	7037	9007	7012	703	71319	7015	7024	7016	7021	9005	8014	8016	780	3004	5014	1006
COVER FOR M	OUNTING		R GUIDE R							1				I	ı		ı									
		KER	92 350		900	1%	POLYSCREEN 550	POLYSCREEN LUMINOUS	ACRYLIC xw AWNING FABRICS		FABRIC COLOU		UR AND NUMBE		METALISATION .		OTHER RAL COLOUR			MOTOR CABLE EXIT						
FABRIC		SUNWORKER	SOLTIS	SCREEN 350	SERGE 600	SERGE									FRONT		BACK					OF G			BACK	
		SUI	SC	sc	SE	SE	POL	8 -	2,8 m without anti-wind							R	ä						SIDE CABLE LOOSE			OOSE
								<u> </u>					CASS	SETTE	ī				1		SIDE	CUIDE	PPACK	ET6	(NO HOLE	
* total exter	nal dimen	sions re	quired.										BRAG		OPTIONAL CASSETTE BRACK											è
			INSTALLATION FOR A SIDE G			UIDE					DRIVE	DRIVE SIDE		-		L SPACER CEILI		NG		mounted	floor		£1	00cm	FIXED LI	ENGTH
No. WIDT		 *	FOR A SIDE G FIXED TO THE I GC30R A B		FRAME	HEIGHT			NTITY	L	<u> </u>						LENGTH A 15-36 B 20-50		to the				12			
							mm		pc	cs.	R									6		M.		LENGTH min. 57		S7mm
1											FRONT				-			₽	B 29-5 C 55-7			22mm	39-45 lu		max. 18	
2					-				-												+				<u> </u>	
3																									<u> </u>	
4																										
5																										
6							_														\perp					
7							_														+					
8																					+					
10																					+					\neg
11																										
12																		_								
13		חחבכ			<u> </u>				<u> </u>									Inc	MARK							
									The Buyer hereby declares that they speak fluent English, understand the statements received and submitted in English, orders submitted, and to have read and accepted General Sales Terms and Conditions, General Warranty Terms and Conditions, Technical-operational documentation and Declaration of performance for external systems, Declaration of Conformity for systems with motor drive and information on safety elements installation for internal systems operated with cord and ball chain, available at https://www.selt.com/dokumenty-en.																	
									ORDERING COMPANY, DATE, SIGNATURE ELECTRIC CONTROL ORDER FORM ATTACHE										CHED							