selt sun protection systems				KI: EF				Έ	_	GROU	JP INST/	ALLATIC	DN - TYPE	OF M	EASURE	MENT										
SYS		EXTERNAL INSTALLATION				L DRI		→ 16←	- AXIS I	MEASURE	MENT -	╧	AXIS	MEASURE		→ F7				rops	rops		D)	/	
SIDE GUIDE				E	FIXED	DETACHABLE	FIXED + WALL GROMMET	DETATCHABLE + WALL GROMMET	<u> </u> <u> </u>	TO			 *-	T	OTAL WID	тн		ELE		DRIVE	× MECHANICAL STOPS	ELECTRONIC STOPS	RATIO		ELERO	SOMFY
		DIMEN		Ħ				BLE +				1		iot app.	to MR103			N	ЕМО	wт		x			SUNTOP	ALTUS WT
BOTTOM BAR			fi	42		D	FIXED +	DETATCHA			0	•			SIDE				NEM	0		х	х	DM45EAF/S	SUNTOP 868	ALTUS RTS
		MAXIN		Š								T			CABLE LOO (NO HOLE)		DSE I		NEMO IO			х	х			SUNILUS in
MARKISO	03	-						тнг	SOUA	RESY	MBOL		RIGH					WHER		сноо	SE THE	SYST	EM TY			
MARKISOLETTE 120 MARKISOLETTE 120 UNDER PLASTER		20 4,0				W	HITE		THA MO	T THE JNTING H CAS	SYSTE 3 BRAC	EM EXI	STS AS , CASSE NTING B	STAN ETTE RACI	NDARD	AS A D TO	SELF-S SUPPC	UPPC RTIN K THE	ORTING G SIDE	g Solu Guide Er Fie	TION (V S). IF T LD WIT	VITHOU HE SY	JT CAS STEM I N REM/	SETTE S TO E	E E MAC	
	OLLECTIC LOURS	0N VSF 240	RAL	RAL		RAL	RAL	RAL 7035	RAL 9006	RAL 7001	RAL 7037	RAL 9007	RAL	DB 703	FSM 71319	RAL 7015	RAL 7024	RAL 7016	RAL	RAL	RAL	RAL 8016	VSR 780		RAL 5014	RAL 1006
SYSTEM C	ONSTRUCT				5001	5010	3010	1000	5000	7001	1001	5001	7012	100		7010	1021	1010	/ /02	5000			100	0004	0014	1000
	OR MOUNTIN OLES		C30R GU	IDE RAIL TYPE A O	RC																					
(ER		92	50	<mark>600</mark>	1%	550		EN OUT					FA	ABRIC	COLOU	JR AND	NUMBI	R				METAL	ISATION	OTHE	R RAL C	OLOUR
FABRIC	SOLTIS 92	SCREEN 350	SERGE 6	SERGE 1%	SCREEN 550	SCREEN	POLYSCREEN 314 BLACK OUT	C ANNING C ANNI													FRONT	BACK				
															SIDE		UIDE BRACKET (OPTIONAL				
													5		R						space ≤1	00cm	CAS		BRAC	KET
* total exter	nal dimens	ions requir	ns required.			INSTALLATION TYPE							FRONT	FRONT							FIXED LENGTH		WALL SPACER CEILIN		ING	
No.		VIDTH* mm			FOR	FOR A SIDE GUIDE IXED TO THE FRAME GC30R		HEIGHT mm		Г	QUAI		dri' Sid	-		GTH dard	LENGTH 39-45 lub 52-51		58 22mm		min. 57mm max. 180mm				00	
1					4																					
2	2																									
3	3																									
4	4																									
5	5																									
6																										
7	-																									
8																										
9																										
10 11																										
12																										
13																										
14																										
15																										
16																										
DELIV	ERY AI	DDRES	S					statemen and acco Conditio for exter informati and ball	nts receive epted Gene ns, Technic nal system on on safe chain, avai	d and sub ral Sales cal-operat s, Declara ty elemen lable at h	mitted in Terms ar tional doc ation of Co tts installa ttps://www	English, ond Condit umentation onformity ation for ir w.selt.con	ent English, orders subi tions, Gene on and Dec for system nfor system n/dokumen ATE, S	mitted, ral Wa laration s with r tems op ty-en.	and to ha rranty Ter n of perfor motor driv perated w	ms and mance e and ith cord	REM		RIC CON		DER FOR					
															IF THE PLEAS	SYSTEM E MARK	IS TO B	E MADE V PER FIEL	/ITH CAS D WITH *	SETTE N X" IN REI	IOUNTIN	g Brack Rea.	KETS,			