
selt sun protection systems

Order form Sunbreaker 210 rotary


Refers to order no:

1. Select the type of blade and plugs




*does not cover the entire surface of the blade

2. Select drive type




3. On which lamella is the drive arm to be mounted, counting from the bottom



	BEIGE		BEIGE		BEIGE		BEIGE		BEIGE		BEIGE WHITE		DARK GREY		ANTHRACITS				BLACK			BLACK	S BROWNES			S	OTHER COLOUR RAL
COLOUR FROM THE SELT COLLECTION	VSR 240	RAL 1015	RAL 1013	RAL 9001	RAL 9010	RAL 9016	RAL 7035	RAL 9006	RAL 7001	RAL 7037	RAL 9007	RAL 7012	DB 703	FSM 71319	RAL 7015	RAL 7039	RAL 7024	RAL 7016	RAL 7021	RAL 7043	RAL 7022	RAL 9005	RAL 8014	RAL 8016	VSR 780	RAL 8003	
Construction Colour																											
Colour of plastics																											

5. Automation


4. Colour select



5.2. Somfy RTS radio control								
	Remote control receiver flush mounted Universal Receiver RTS (FD)							
	Remote control receiver Universal Slim Reciver RTS Stak3/Stas3 (FD)							
(<u>+</u>)++	Single-channel remote control Situo 1 PURE (FP)							
[<u>×@×</u>]6	Five-channel remote control Situo 5 PURE <mark>(FU)</mark>							

5.3. Somfy IO radio control							
	Remote control receiver Pergola remote control receiver Slim receiver io (N1)						
	Single-channel remote control Situo 1 io PURE II <mark>(3M)</mark>						
(<u><</u>)>15	Five-channel remote control Situo 5 io PURE II <mark>(35)</mark>						

7. Determine the direction of rotation of the blades



The above drawing should be interpreted as a front projection of the system. Mounting of the SUNBREAKER 210 system can be carried out in a niche or on a substructure. NO FACADE MOUNTING BRACKETS!!!

There is a choice of lamellas that open clockwise or counterclockwise, thus determining the side in which the lamellas open.

8. Specify the dimensions, number and side of the drive and the direction of opening of the lamellas.

	JANTITY [szt.]	WIDTH [mm]	HEIGHT [mm]	DIRECTIONS OF OPENING THE BLADES CLOCKWISE / COUNTECLOCKWISE	DRIVE MANUAL/MOTOR	DRIVE LEVER CONNECTION BLADE NUMBER
1						
2						
3						
4						
5						
6						
7						

Mounting of the SUNBREAKER 210 system can be carried out in a niche or on a substructure. NO FACADE MOUNTING BRACKETS!!!

Delivery address:		
statements made and of the order placed ar General Terms and Cor of Guarantee and the T Conditions of Sale, th the Technical and Op of Performance. Decla systems, the Declarat operated systems, the	received in English. I d has familiarised hi ditions of Sale, the Go fechnical and Operat e General Terms an operational Documen aration of Performar cion of Conformity Declaration of Confor the Information She use Chain and Cord S	English, understands the He understands the content imself with and accepts the eneral Terms and Conditions ional the General Terms and d Conditions of Guarantee, tation and the Declaration ree. In the case of outdoor in the case of for motor- ormity in the case of motor- set for Mounting of Securing Systems, available at:
SIGNATURE:	DATE:	SIGNATURE:

Remarks:	