

ROOF MODULE SB400

RIGHT FRONT						
DIRECTION OF OPI						
CLOCKWISE CLOCKWISE						
according to the drawing REAR FRONT						
	g to the drawing					
SYSTEM		mm L	STANDARD CONSTR	RUCTION SLATS		
SYSTEM WIDTH max 3830			mm B	RAL9016 MAT		
IIIdA 3630				FSM71319		
QUANTITY				OTHER SELT COLLECTION		
OPTIONAL GUTTER	LENGTH		mm	QUANTITY		
DRIV	DRIVE AT THE LEFT DRIVE AT THE RIGHT SIDE					
DRIVE OPERATION Switch		REMARKS				
RTS io						
SLIM receiver	Pergola Slim receiver io + plug					
TELIS 1	Situo 1 io	DELIVERY ADDRESS				
TELIS 4	Situo 5 io					
TELIS 1 SOLIRIS	Situo 1 A/M io					
TELIS 4 SOLIRIS	Situo 5 VAR A/M io	The Division Land	obu doclares *b -* *!	overpool fluorit Freish	I the statements reserved and	
Eolis RTS 230V	Eolis io 230V	The Buyer hereby declares that they speak fluent English, understand the statements received and submitted in English, orders submitted, and to have read and accepted General Sales Terms and Conditions, General Warranty Terms and Conditions, Technical-operational documentation and Declaration of performance for external systems, Declaration of Conformity for systems with motor				
Sunis WireFree	Sunis Wirefree					
Sensor sensor io drive a			ive and information on safety elements installation for internal systems operated with cord and ball			
I ICONNEXOUNDOXIO I			chain, available at www.selt.com/doc-en. COMPANY, DATE, SIGNATURE			
SELT Sp. z o.o. FC / SELT / 086 - 4 - EN						